



## 12ft

### ECO MOBILE WELFARE UNITS

Secure welfare space in an ideal mobile unit.

Meeting HSE & CDM requirements, the 12ft mobile welfare is suitable for accommodating six people.



#### Main Features







- Warm water supplied by an on-board heating system
- Air blown heating system
- Comfortably sits up to 6 people
- Secured in less than 3 minutes
- High security doors & windows
- Meets HSE & CDM requirements
- Removable low level lifting eyes
- Fully galvanised chassis

#### Rooms

1. Welfare Area
2. Toilet Area
3. Warm Room / Generator Area

Please see details on next page.

# Features & Benefits

 <b>6</b> Canteen for 6	<b>1700kg</b> Unladen Weight <b>1815kg</b> Gross Weight	 <b>W 2300</b> <b>L 4920</b> Dimensions (mm)
<b>up to 60%</b> CO2 Emissions Savings	 <b>Toilet 280L</b> Toilet Waste Capacity	 <b>20L</b> Waste  <b>20L</b> Wash Water Capacity
 Quiet Generator	<b>up to 60%</b> Reduced Fuel Costs	<b>Reduced</b> Generator Service Cost Saving



## 1. Welfare Area

- Table and bench seating for up to 6 people
- 12V LED lighting with PIR
- Air blown heating system
- Microwave and kettle - both hard-wired
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w warm water tap
- 12V cooler box (optional)
- Single inverter powered socket & USB connection
- Consumer board c/w RCD & MCB's
- Generator start panel c/w hour run meter
- Fresh & waste water containers (20L cap each)
- Large stainless steel sink c/w warm water tap
- Carbon monoxide monitor and smoke alarm
- Paper towels, liquid soap and cup dispenser
- 130Amp hour battery/charger & battery guard

## 2. Toilet Area

- Plastic recirculating toilet c/w ventilation pipe
- Toilet tank size: 280L
- Toilet roll holder
- 12V LED lighting with PIR
- Forearm pedestal wash basin c/w warm water tap
- Warm water supplied by on-board heating system
- Liquid soap and paper towel dispenser

## 3. Warm Room / Generator Area

- 12V LED lighting PIR
- Air blown heating system
- Coat hooks

- Ventilation panel
- 6kVA diesel generator with exhaust venting
- Access to fuel tank with separate fuel level gauge (58L cap)
- Fuel active system
- Generator start battery

